

CLIMATEST CH 150 Climatic chamber (150 lt)

Item Code: 41101412



DATA SHEET

Features

Accuracy (Temperature)	± °C
Power supply	220 ±10% V
Capacity	150 L
Maximum shelf load	10 kg
Security class	3.1
Dimension	690 x 790 x 1520 mm
Internal dimensions	550 x 405 x 670 mm
Dimension (external tank)	370 x 340 x 560 mm
Display	Digital backlit alphanumeric LCD
Minimum distance between shelves	45 mm
Humidity fluctuation	± 3% (10...70°C / 55...95% RH)
Frequency	50/60 Hz
Warranty	2 anni
Image 2	https://app.onpage.it/api/storage/d2b7bc95ef0668a2db2946cad4a5778b7af47
Working method	Forced ventilation
Name	CH 150
Regulations	2006/95/EC - 2004/108/EC - EN61326-1:2006 - EN61010-1:2010
Number of shelves	3
Homogeneity in space (with umidity)	±1,5 °C (+10...+70 °C / 55...95 %RH)
Homogeneity in space (without umidity)	±0,5 °C
Weight	145 kg
Absorbed power	2200 W
Programs	Customisable programmes with ramps from 1 to 100 steps and Fix
Coolant quantity	280 g
Coolant type	R1234ZE
Resolution	0,01 °C / 0,1% RH
Data transfer	Numerical or graphic via printer receipt
Stability over time without humidity	±0,2 °C
Working temperature	+10...+70 °C (con umidità) / 0...+85 °C (senza umidità) °C

Timer	(99:59 e Fix) digitale con data ed ora per funzioni GLP hh:mm
Temperature variation on time in 1 point (with humidity)	±0,5 °C
Useful volume	150 L